



# FRONIUS TAURO



## PRELIMINARY DATA

### TECHNICAL DATA FRONIUS TAURO - PRESERIES

INPUT DATA	FRONIUS TAURO 50-3-D FRONIUS TAURO 50-3-P	FRONIUS TAURO ECO 50-3-D FRONIUS TAURO ECO 50-3-P	FRONIUS TAURO ECO 100-3-D FRONIUS TAURO ECO 100-3-P
Number of MPP trackers	3	1	1
Max. input current ( $I_{dc \max}$ )	36 / 36 / 72 A	87,5 A	175 A
DC input voltage range ( $U_{dc \min} - U_{dc \max}$ )	200 - 1000 V		580 - 1000 V
Feed-in start voltage ( $U_{dc \text{ start}}$ )	400 V		650 V
Usable MPP voltage range	400-930 V		580-930 V
Number of DC connections	D: 3/4/7 <sup>1)</sup> , P: 3 <sup>2)</sup>	D: 14/0/0 <sup>1)</sup> , P: 2 <sup>2)</sup>	D: 22/0/0 <sup>1)</sup> , P: 3 <sup>2)</sup>
Max. PV generator power ( $P_{dc \max}$ )		75kWp	150kWp

OUTPUT DATA	FRONIUS TAURO 50-3-D FRONIUS TAURO 50-3-P	FRONIUS TAURO ECO 50-3-D FRONIUS TAURO ECO 50-3-P	FRONIUS TAURO ECO 100-3-D FRONIUS TAURO ECO 100-3-P
AC nominal output ( $P_{ac,n}$ )	50,000 W	50,000 W	100,000 W
Max. AC output current ( $I_{ac \max}$ )		75 A	150 A
Grid connection (voltage range)		3~ NPE 380/220V or 3~ NPE 400/230V	
Frequency (Frequency range)		50 Hz / 60 Hz (45 - 65 Hz)	
Total harmonic distortion		< 3 %	
Power factor ( $\cos \phi_{ac,r}$ )		0 - 1 ind. / cap.	

GENERAL DATA	FRONIUS TAURO 50-3-D FRONIUS TAURO 50-3-P	FRONIUS TAURO ECO 50-3-D FRONIUS TAURO ECO 50-3-P	FRONIUS TAURO ECO 100-3-D FRONIUS TAURO ECO 100-3-P
Dimensions (height x width x depth)		644mm x 1038mm x 316mm	
Weight	93 kg	80 kg	105 kg
Degree of protection		Power electronics area: IP66 / DC connection area: IP66 / AC connection area: IP65	
Protection class		1	
Overvoltage category (DC / AC)		2 / 3	
Inverter concept		Transformerless	
Cooling		Regulated air cooling	
Installation		Indoor and outdoor installation	
Ambient temperature range		-40 - +65 °C	
Permitted humidity		0 to 100 % (condensing)	
DC connection technology		MC4 whips <sup>1)</sup> , V-clamps <sup>2)</sup>	
AC connection technology		V-clamps	
Certificates and compliance with standards		IEC62109-1:2010, IEC62109-2:2011, DIN V VDE 0126-1-1:2006	

EFFICIENCY	FRONIUS TAURO 50-3-D FRONIUS TAURO 50-3-P	FRONIUS TAURO ECO 50-3-D FRONIUS TAURO ECO 50-3-P	FRONIUS TAURO ECO 100-3-D FRONIUS TAURO ECO 100-3-P
Max. efficiency	98.2 %	98.5 %	98.5 %
European efficiency ( $\eta_{EU}$ )	97.4 / 97.8 / 97.5 %	98.2 / 98.0 / 97.5 %	98.2 / 98.0 / 97.5 %

PROTECTION DEVICES	FRONIUS TAURO 50-3-D FRONIUS TAURO 50-3-P	FRONIUS TAURO ECO 50-3-D FRONIUS TAURO ECO 50-3-P	FRONIUS TAURO ECO 100-3-D FRONIUS TAURO ECO 100-3-P
DC insulation measurement		Yes	
Overload behavior		Operating point shift, power limitation	
Reverse polarity protection		Yes	

<sup>1)</sup> direct <sup>2)</sup> precombined

Fronius International GmbH  
Froniusplatz 1  
4600 Wels  
Austria  
pv-sales@fronius.com  
www.fronius.com